

# INSTALLATION INSTRUCTIONS

## MODELS MO-1, MO-2

Screw the lower portion of the mast into the desired ball mount or bumper mount assembly, using the 3/8" lockwasher.

Twist and pull down on the knurled sleeve to lower the mast to its horizontal position for resonator changing or adjustment.

To lock the mast in its vertical position, push the knurled sleeve up so that it is touching the angle bracket. Lower and secure the mast before driving into the garage.

### ACCESSORIES

The Hustler Model QD-2, all stainless steel quick disconnect, may be added between mount and mast.

To alleviate possible damage to the antenna from striking low branches etc., install a Hustler Model RSS-2 resonator spring between resonator and mast.

Installation of either or both accessories will not disrupt or change antenna tuning to any detectable degree.

### SIX METER

The Hustler Models MO-1 and MO-2 masts are 54" in length, 1/4 wave length at six meters and are designed to offer optimum mobile antenna performance and broad band response due to the large diameter conductor. When operating on six, it is not necessary to remove the low band resonator.

Keep the mast clean and polished. Lubricate and operate the hinge section frequently to insure proper operation.

### NEW-TRONICS ANTENNA CORPORATION LIMITED WARRANTY

New-Tronics Antenna Corp. warrants its products to be free of defects in material and workmanship and extends this warranty under intended use and normal service conditions to the original owner for a period of one year from the date of purchase. This warranty does not apply to any product that has been repaired or altered in any manner and is void for any damage due to accident, neglect, unreasonable use, improper installation, or any other cause not arising out of defects in material or workmanship.

The obligations of New-Tronics Antenna Corporation are limited to repairing or replacing, at its option, any product or part that is returned to the factory; all transportation charges prepaid, accompanied by proof of purchase, and upon examination reveals to have been defective within the warranty period stated above. New-Tronics Antenna Corp. does not assume nor is any person authorized to assume for it, any obligations other than that herein stated.

Any implied warranties, including but not limited to fitness for a particular purpose, is limited in duration for the above one year period. New-Tronics Antenna Corp. shall not be liable under this warranty, or any implied warranty, for loss of use of the product or for other consequential loss or damage incurred by the purchaser. Some states do not allow the exclusion or limitation of implied warranties of consequential damages and so the above exclusions or limitations may not apply in those states. This warranty gives you special legal rights and you may have other rights that vary from state to state.

Kit No. 5514

MO-1, MO-2 2895-1

Rev. 1, 2/98




New-Tronics Antenna Corp.  
One Newtronics Place  
Mineral Wells, TX 76067-9563  
940-325-1386

Printed in U.S.A.

**Note:** The mast assembly is part of the total radiating system, and should not be located parallel to other metal parts of the vehicle.


**Model MO-1**  
with shorter lower section.  
For installation on rear deck or fender.

**MAST IN HORIZONTAL POSITION**



**MODEL MO-2**  
Mast with longer lower section.  
For installation on bumper.

For deck or fender mounting position the antenna approximately midway between rear window and rear of car.



**Model BM-1**  
Bumper mount

